


HRI0806SPI High-Reliability Shielded Power Inductor



Features

- Tin-Lead solder termination finish.
- Shielded construction for low radiation.
- Metal alloy powder core for high saturation current.



Applications

- Aerospace
- Avionics
- Military


Electrical Characteristics @ +25 °C

AEM Part No.	Inductance @500kHz/0.25V		DCR (mΩ) Typ.	DCR (mΩ) Max.	I _{rms} (A) Typ.	I _{sat} (A) Typ.
	L(uH)	Tol. %				
HRI0806SPI-R47Mxx	0.47	20	29	40	3.60	4.50
HRI0806SPI-R56Mxx	0.56	20	42	57	3.00	4.00
HRI0806SPI-1R0Mxx	1.0	20	57	70	2.60	3.40
HRI0806SPI-1R5Mxx	1.5	20	83	110	2.10	2.80
HRI0806SPI-2R2Mxx	2.2	20	137	168	1.60	2.20
HRI0806SPI-3R3Mxx	3.3	20	202	225	1.40	1.90
HRI0806SPI-4R7Mxx	4.7	20	315	360	1.10	1.50

Product Dimensions



Recommended Pad Layout



DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

HRI0806SPI High-Reliability Shielded Power Inductor


Standard Screening Options

- Option 1: 100% visual inspection per MIL-PRF-83446, MIL-STD-981.
- Option 2: Group A and B Screening per MIL-PRF-83446, MIL-STD-981.
- Option 3: Group A, B, and C Screening per MIL-PRF-83446, MIL-STD-981.
- Option 4: Group A, B, and Qualification Screening per MIL-PRF-83446, MIL-STD-981.

Note: See AEM detail specification for more details.

Part Number Identifier

HRI 0806SPI 2R2M x x



General Specifications and Materials

- 1- Operating temperature:..... -40°C to +125°C (Temperature rise included).
- 2- Storage temperature:..... (Component) -40°C to +125°C.
- 3- Temperature rise:..... 40°C at rated Irms*.
- 4- Inductance drops:..... 30% at Isat.
- 5- Moisture sensitivity level:..... MSL=1
- 6- ESD Classification (HBM):N/A
- 7- Core:Metal alloy powder.
- 8- Wire:Enameled copper.
- 9- Terminal finish:Tin/Lead (Sn/Pb).

* Note: Part temperature should be verified in the end application. Circuit design, component, PCB traces size and thickness, airflow and other cooling provisions affect the part temperature.